



# SNR BEARING CORP.OF AMERICA



skf SAF 22620 x 3.5/16 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 22620 x 3.5/16

SAF 22620 x 3.5/16 Bearing 2D drawings and 3D CAD models

$d_a$	84.138 mm
$D_a$	215.001 mm
$C_a$	82.804 mm
$A_1$	120.65 mm
$A_2$	187.325 mm
S	4.763 mm
$b_a$	57.944 mm
H	258.762 mm
$H_1$	133.35 mm
$H_2$	53.975 mm
J min.	336.55 mm
J max.	368.3 mm
$J_1$	69.85 mm
L	419.1 mm
$N_1$	22.225 mm
$R_1$	79.375 mm
$R_2$	30.163 mm
$R_G$	1/2 NPT
$P_G$	1/4 NPT
h	51.594 mm
Housing	SAF 620
Stabilizing ring	SR-24-20
Labyrinth ring	2 x LOR 100
End plug (suffix Y)	EPR 12
Bearing limiting speed	3000 r/min



## SNR BEARING CORP.OF AMERICA

P <sub>60°</sub>	185 kN
P <sub>90°</sub>	111 kN
P <sub>120°</sub>	72.5 kN
P <sub>150°</sub>	66.7 kN
P <sub>180°</sub>	81.4 kN
P <sub>a</sub>	21.8 kN
Mass pillow block	51.3 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	1220 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	379.89 g