



SNR BEARING CORP.OF AMERICA



skf SSAFS 22516 x 2.5/8 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SSAFS 22516 x 2.5/8 T

SSAFS 22516 x 2.5/8 T Bearing 2D drawings and 3D CAD models

d_a	66.675 mm
D_a	140 mm
C_a	42.799 mm
A_1	88.9 mm
A_2	215.9 mm
S	4.763 mm
b_a	33.337 mm
H	174.625 mm
H_1	88.9 mm
H_2	31.75 mm
L	330.2 mm
R_1	53.181 mm
R_2	21.431 mm
R_G	3/8 NPT
P_G	1/8 NPT
h	31.75 mm
Housing	SSAFS 516
Bearing	22216 EK
Adapter sleeve assembly	SNW 16x2.5/8
Stabilizing ring	SR-16-13
Taconite seal	TER 43
End plug (suffix Y)	EPR 8
Max. speed for Taconite seal	1150 r/min
P_{60°	138 kN
P_{90°	82.7 kN



SNR BEARING CORP.OF AMERICA

P _{120 °}	49.8 kN
P _{150 °}	44.5 kN
P _{180 °}	52.5 kN
P _a	7.83 kN
Mass pillow block	21.8 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N · m
Cap bolt, SAE grade	8
Initial grease fill	87.885 g