




SNR BEARING CORP.OF AMERICA



skf SAF 23056 KAT x 10 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 23056 KAT x 10

SAF 23056 KAT x 10 Bearing 2D drawings and 3D CAD models

d_a	254 mm
D_a	419.999 mm
C_a	147.803 mm
A_1	228.6 mm
A_2	419.1 mm
b_a	100.806 mm
H	495.3 mm
H_1	250.825 mm
H_2	101.6 mm
J min.	666.75 mm
J max.	749.3 mm
J_1	139.7 mm
L	869.95 mm
N_1	41.275 mm
R_1	163.512 mm
R_2	50.8 mm
R_G	1 NPT
P_G	1/4 NPT
h	73.025 mm
Housing	SAF 056 KAUB
Stabilizing ring	2 x A8819
Taconite seal	TER 568
End plug (suffix Y)	X-5217-2
Max. speed for Taconite seal	310 r/min
P_{60°	449 kN



SNR BEARING CORP.OF AMERICA

P _{90°}	271 kN
P _{120°}	169 kN
P _{150°}	151 kN
P _{180°}	185 kN
P _a	89 kN
Mass pillow block	324 kg
Cap bolt	4 x 1 1/2-6 UNC
Cap bolt recommended tightening torque	1017 N · m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	3515.4 g