




SNR BEARING CORP.OF AMERICA



skf SAF 1516 x 2.5/8 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 1516 x 2.5/8 T

SAF 1516 x 2.5/8 T Bearing 2D drawings and 3D CAD models

d_a	66.675 mm
D_a	140 mm
C_a	42.799 mm
A_1	88.9 mm
A_2	209.55 mm
b_a	30.163 mm
H	169.863 mm
H_1	88.9 mm
H_2	31.75 mm
J min.	244.475 mm
J max.	279.4 mm
L	330.2 mm
N_1	22.225 mm
R_1	53.181 mm
R_2	21.431 mm
R_G	3/8 NPT
P_G	1/8 NPT
h	49.212 mm
Housing	SAF 516
Bearing	1216 K
Adapter sleeve assembly	SNW 16x2.5/8
Stabilizing ring	2 x SR-1516
Taconite seal	TER 43
End plug (suffix Y)	EPR 8
Max. speed for Taconite seal	1150 r/min



SNR BEARING CORP.OF AMERICA

P _{60°}	83.2 kN
P _{90°}	49.8 kN
P _{120°}	30.2 kN
P _{150°}	26.7 kN
P _{180°}	31.6 kN
P _a	6.23 kN
Mass pillow block	16.4 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	149.1 N · m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	175.77 g