




SNR BEARING CORP.OF AMERICA



skf FSAF 22516 x 2.5/8 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. FSAF 22516 x 2.5/8 T

FSAF 22516 x 2.5/8 T Bearing 2D drawings and 3D CAD models

d_a	66.675 mm
D_a	140 mm
C_a	42.799 mm
A_1	88.9 mm
A_2	209.55 mm
S	4.763 mm
b_a	34.131 mm
H	169.863 mm
H_1	88.9 mm
H_2	31.75 mm
J min.	244.475 mm
J max.	279.4 mm
J_1	53.975 mm
L	330.2 mm
N_1	19.05 mm
R_1	53.181 mm
R_2	21.431 mm
R_G	3/8 NPT
P_G	1/8 NPT
h	31.75 mm
Housing	FSAF 516
Bearing	22216 EK
Adapter sleeve assembly	SNW 16x2.5/8
Stabilizing ring	SR-16-13
Taconite seal	TER 43



SNR BEARING CORP.OF AMERICA

End plug (suffix Y)	EPR 8
Max. speed for Taconite seal	1150 r/min
P _{60°}	60.5 kN
P _{90°}	36 kN
P _{120°}	21.8 kN
P _{150°}	19.6 kN
P _{180°}	23.1 kN
P _a	7.83 kN
Mass pillow block	17.4 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	149.1 N · m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.625 in
Initial grease fill	87.885 g