



SNR BEARING CORP.OF AMERICA



skf SAF 23026 KAT x 4.3/8 SAF and SAW
pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 23026 KAT x 4.3/8

SAF 23026 KAT x 4.3/8 Bearing 2D drawings and 3D
CAD models

d_a	111.125 mm
D_a	200 mm
C_a	62.789 mm
A_1	120.65 mm
A_2	234.95 mm
b_a	51.594 mm
H	239.713 mm
H_1	125.425 mm
H_2	50.8 mm
J min.	320.675 mm
J max.	368.3 mm
J_1	69.85 mm
L	419.1 mm
N_1	22.225 mm
R_1	67.945 mm
R_2	31.75 mm
R_G	3/8 NPT
P_G	1/4 NPT
h	42.862 mm
Housing	SAF 026 KA
Bearing	23026 CCK/W33
Adapter sleeve assembly	SNW 3026x4.3/8
Stabilizing ring	2 x 38151-26
Taconite seal	TER 116
End plug (suffix Y)	EPR 15



SNR BEARING CORP.OF AMERICA

Max. speed for Taconite seal	700 r/min
P _{60°}	149 kN
P _{90°}	89 kN
P _{120°}	55.6 kN
P _{150°}	50.7 kN
P _{180°}	60.9 kN
P _a	20.2 kN
Mass pillow block	32.2 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N · m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	232.47 g