



# SNR BEARING CORP.OF AMERICA



skf FSAF 22516 x 2.3/4 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. FSAF 22516 x 2.3/4 T

FSAF 22516 x 2.3/4 T Bearing 2D drawings and 3D CAD models

$d_a$	69.85 mm
$D_a$	140 mm
$C_a$	42.799 mm
$A_1$	88.9 mm
$A_2$	209.55 mm
S	4.763 mm
$b_a$	34.131 mm
H	169.863 mm
$H_1$	88.9 mm
$H_2$	31.75 mm
J min.	244.475 mm
J max.	279.4 mm
$J_1$	53.975 mm
L	330.2 mm
$N_1$	19.05 mm
$R_1$	53.181 mm
$R_2$	21.431 mm
$R_G$	3/8 NPT
$P_G$	1/8 NPT
h	31.75 mm
Housing	FSAF 516
Stabilizing ring	SR-16-13
Taconite seal	TER 45
End plug (suffix Y)	EPR 8
Max. speed for Taconite seal	1150 r/min



## SNR BEARING CORP.OF AMERICA

P <sub>60°</sub>	60.5 kN
P <sub>90°</sub>	36 kN
P <sub>120°</sub>	21.8 kN
P <sub>150°</sub>	19.6 kN
P <sub>180°</sub>	23.1 kN
P <sub>a</sub>	7.83 kN
Mass pillow block	17.4 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	149.1 N · m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.625 in
Initial grease fill	87.885 g